


# PF- Petpak322S

BOPET Film - General Films



**Application:** Transparent film used for Flexible packaging application, specially designed for hot filling, sterilization and pasteurization Processes. The coated layer gives outstanding adhesion to metal and a wide range of inks. Other side of film can also be non-treated (PF-Petpak 323 S).

Technical Data	Specification	Unit	Value				
		Thickness	µm	8	10	12	23
PF- Petpak322S	Yield	m <sup>2</sup> / Kg	89.3	74.1	59.5	31.1	19.8
	Unit weight	g/m <sup>2</sup>	11.2	14	16.8	32.2	50.4

Logistic Data	MOQ (Minimum Order Quantity)
PF- Petpak322S	40ft HC Container

## Benefits & Options

- \* Transparent
- \* Special Chemical Coated (1 Side)
- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (EU) No 453/2010
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)