


PF-Petmet181HB

BOPET Film – General Films



Application : High barrier metallized film used for flexible packaging; specifically designed for hot filling, sterilization and pasteurization Processes. Superior metal adhesion is obtained with metallizing on special coated layer. Non-treated film is available (Petmet 180 HB).

Technical Data	Specification	Unit	Value				
	Thickness	μm	8	10	12	23	36
PF-Petmet181HB	Yield	m ² / Kg	89.3	74.1	59.5	31.1	19.8
	Unit weight	g/m2	11.2	14	16.8	32.2	50.4

Logistic Data	MOQ (Minimum Order Quantity)
PF-Petmet181HB	40ft HC Container

Benefits & Options

- * Metalizing on special coating
- * Metallized
- * High barrier Metallized
- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (EU) No 453/2010
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)