




PF-Petpak223S

BOPET Film - General Films



Application: Coated film for flexible packaging; applicable in printing, metallizing, lamination and coating. The coated layer gives excellent adhesion to a wide range of inks and improves metal bonding in metallization. The other side of film can also be corona treated (PF-Petpak 222 S).

Technical Data	Specification	Unit	Value				
	Thickness	μm	8	10	12	23	36
PF-Petpak223S	Yield	m² / Kg	89.3	74.1	59.5	31.1	19.8
	Unit weight	g/m2	11.2	14	16.8	32.2	50.4

Logistic Data	MOQ (Minimum Order Quantity)
PF-Petpak223S	40ft HC Container

Benefits & Options

- * Transparent
- * Chemical Coated (1 Side)
- * Conformity Declaration (FDA/ EU)

- * Material Safety Data Sheet (EU) No 453/2010
- * Food Grade Material / FDO Certified
- Minimum order can include multiple types (negotiable for trials)