


PF-POLEX220ACDW

BOPP Film – Over Wrapping



Application : Specially designed to be used on high speed over wrapping machines. This film has high shrink property to provide a tight wrap. Also It has a good antistatic property to prevent dust accumulation on film surface.

Technical Data	Specification	Unit	Value
	Thickness	µm	20
	Yield	m ² / Kg	54.9
	Unit weight	g/m2	18.2
PF-POLEX220ACDW			

Logistic Data	MOQ (Minimum Order Quantity)
	40ft HC Container
PF-POLEX220ACDW	

Benefits & Options

- * Transparent
- * High Shrinkage
- * Heat Sealable (2 side)
- * Non Treated
- * Low SIT

- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material and FDO Certified
- * Minimum order can include multiple types (negotiable for trials)