


PF-POLEX220AGD

BOPP Film – Over Wrapping



Application : Specially designed to be used on high speed over wrapping machines. It has a good antistatic property to prevent dust accumulation on film surface.

Technical Data	Specification	Unit	Value
	Thickness	μm	20
PF-POLEX220AGD	Yield	m ² / Kg	54.9
	Unit weight	g/m2	18.2

Logistic Data	MOQ (Minimum Order Quantity)
PF-POLEX220AGD	40ft HC Container

Benefits & Options

- * Transparent
- * Heat Sealable (2 side)
- * Non Treated
- * Low SIT

- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material and FDO Certified
- * Minimum order can include multiple types (negotiable for trials)