




PF-Petlid322S

BOPET Film - Lid Films



Application: Non-sealable Isotropic film used for lidding applications like dairy products, ready meals, fruits, salads and beverages. One side is chemically modified to improve printability.

Technical Data	Specification	Unit	Value			
	Thickness	μm	12	23	36	50
PF-Petlid322S	Yield	m² / Kg	59.5	31.1	19.8	14.3
	Unit weight	g/m2	16.8	32.2	50.4	70

Logistic Data	MOQ (Minimum Order Quantity)
PF-Petlid322S	40ft HC Container

Benefits & Options

- * Chemical coated (1 side)
- * Transparent
- * Isotropic
- * Conformity Declaration (FDA/ EU)

- * Material Safety Data Sheet (EU) No 453/2010
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)