


# PF-Petstam150R

BOPET Film - Hot Stamp



**Application :** Matt thermo-stabilized film used for hot stamping application such as transferring the printing patterns to Edge banding, PVC cornice, MDF design and etc. high matt appearance of the film can also be supplied as Petstam 150QR.

Technical Data	Specification	Unit	Value	
	Thickness	μm	18	23
	Yield	m <sup>2</sup> / Kg	39.6	31
	Unit weight	g/m2	25.2	32.2
PF-Petstam150R				

Logistic Data	MOQ (Minimum Order Quantity )
PF-Petstam150R	40ft HC Container

## Benefits & Options

- \* Matt
- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (EU) No 453/2010
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)