


# PF-Polable132LIQ

BOPP Film – In Mold Label



**Application :** In-mold labeling, suitable for sheet-fed and roll fed printing. This film can also be used for other kinds of applications such as cut & stack.

Technical Data	Specification	Unit	Value
	Thickness	µm	57
	Yield	m <sup>2</sup> / Kg	19.7
	Unit weight	g/m2	50.7
PF-Polable132LIQ			

Logistic Data	MOQ (Minimum Order Quantity )
	40ft HC Container
PF-Polable132LIQ	

## Benefits & Options

- \* Solid White
- \* Treated (2 Side)
- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (91/155EEC)
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)