


PF-Polable132LIV

BOPP Film – In Mold Label



Application : In-mold labeling, suitable for sheet-fed and roll fed printing. This film can also be used for other kinds of applications such as cut & stack.

Technical Data	Specification	Unit	Value
	Thickness	μm	57
	Yield	m ² / Kg	18.3
	Unit weight	g/m2	54.7
PF-Polable132LIV			

Logistic Data	MOQ (Minimum Order Quantity)
PF-Polable132LIV	40ft HC Container

Benefits & Options

- * Matt
- * Solid White
- * Treated (2 Side)
- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)