



PF-Polable142LIT

BOPP Film – In Mold Label



Application : High yield BOPP film for In-mold labeling, Specially designed for high speed sheet fed converting machine. This film can also be used for other kinds of applications such as cut & stack.

Technical Data	Specification	Unit	Value		
	Thickness	μm	50	60	70
PF-Polable142LIT	Yield	m ² / Kg	36.4	30.3	26
	Unit weight	g/m2	27.5	33	38.5

Logistic Data	MOQ (Minimum Order Quantity)
PF-Polable142LIT	40ft HC Container

Benefits & Options

- * White Voided
- * Treated (2 Side)
- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)