


PF-Polable142LIV

BOPP Film – In Mold Label



Application : In-mold labeling, suitable for sheet-fed and roll fed printing. This film can also be used for other kinds of applications such as cut & stack. It can be used instead of CPP IML films for rather big containers.

Technical Data	Specification	Unit	Value	
	Thickness	µm	60	70
	Yield	m ² / Kg	22.2	18.7
	Unit weight	g/m2	45	53.2
PF-Polable142LIV				

Logistic Data	MOQ (Minimum Order Quantity)
PF-Polable142LIV	40ft HC Container

Benefits & Options

- * White Voided
- * Treated (2 Side)
- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)