




## PF-Polable152LIQ

BOPP Film - In Mold Label



Application: In-mold labeling, suitable for sheet-fed and roll fed printing. This film can also be used for other kinds of applications such as cut & stack.

Technical Data	Specification	Unit	Value
	Thickness	μm	57
PF-Polable152LIQ	Yield	m² / Kg	19.9
	Unit weight	g/m2	50.2

Logistic Data	<b>MOQ</b> (Minimum Order Quantity )	
PF-Polable152LIQ	40ft HC Container	

## **Benefits & Options**

- \* Mat
- Treated (2 Side)
- Conformity Declaration (FDA/ EU)

- \* Material Safety Data Sheet (91/155EEC)
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)