


PF-Polcoat432SAL

BOPP Film - Self-Adhesive Label



Application : Self-adhesive label (hot-melt or acrylic) production. This film can also be used for other kinds of applications such as cut & stack. Primer coated films are used for better printing. Non-coated type of this film, Polable 132 LIV, can be supplied upon request.

Technical Data	Specification	Unit	Value
	Thickness	μm	57
PF-Polcoat432SAL	Yield	m ² / Kg	19.7
	Unit weight	g/m2	50.7

Logistic Data	MOQ (Minimum Order Quantity)
PF-Polcoat432SAL	40ft HC Container

Benefits & Options

- * Solid White
- * Primer Coated (1 Side)
- * Corona Treated (1 Side)
- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)