


# PF-Polcoat452SAL

BOPP Film - Self-Adhesive Label



**Application :** Self-adhesive label (hot-melt or acrylic) production. This film can also be used for other kinds of applications such as cut & stack. Primer coated films are used for better printing. In this product Primer applied on matt side of the film.

Technical Data	Specification	Unit	Value
	Thickness	µm	57
	Yield	m <sup>2</sup> / Kg	19.9
	Unit weight	g/m2	50.2
PF-Polcoat452SAL			

Logistic Data	MOQ (Minimum Order Quantity )
	40ft HC Container
PF-Polcoat452SAL	

## Benefits & Options

- \* Matt
- \* Primer Coated (1 Side)
- \* Corona Treated (1 Side)
- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (91/155EEC)
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)