


# PF-Polcoat482SAL

BOPP Film - Self-Adhesive Label



**Application :** Self-adhesive label (hot-melt or acrylic) production. This film can also be used for other kinds of applications such as cut & stack. Primer coated films are used for better printing. Non-coated type of this film, Polable 182 SAL, can be supplied upon request.

Technical Data	Specification	Unit	Value	
	Thickness	µm	50	60
	Yield	m <sup>2</sup> / Kg	22	18.3
	Unit weight	g/m2	45.5	54.6
PF-Polcoat482SAL				

Logistic Data	MOQ (Minimum Order Quantity )
PF-Polcoat482SAL	40ft HC Container

## Benefits & Options

- \* Metalized
- \* Primer Coated (1 Side)
- \* Corona Treated (1 Side)
- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (91/155EEC)
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)