

PF-Poler 241 D

BOPP Film – Flexible Packaging

TREATED
(1 SIDE)


WHITE
VOIDED

HEAT
SEALABLE
(2 SIDE)

LOW
SIT



Treated Heat Sealable Layer
Special OPP Layer
White Voided OPP Layer
Special OPP Layer
Special Heat Sealable Layer



Application : General purpose, for ice-cream, wafers, snacks, biscuits and packaging applications, wherever pearlized effect is required. White color of this film eliminates the need for white base color print. Heat sealing threshold of PF-Poler 241 D is lower than 105 °C.

Technical Data	Specification	Unit	Value		
	Thickness	µm	25	30	35
PF-Poler 241 D	Yield	m ² / Kg	52.9	47.6	40.8
	Unit weight	g/m2	18.9	21	24.5

Logistic Data	MOQ (Minimum Order Quantity)
PF-Poler 241 D	40ft HC Container

Benefits & Options

- * White voided
- * Heat Sealable (2 side)
- * Treated (1 Side)
- * Low SIT

- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)