


# PF-Polet 381 D

BOPP Film – Flexible Packaging



**Application :** For packaging of snacks, chips, biscuits, ice-creams, coffee, etc where the barrier properties are required. It can be printed and laminated with BOPP, BOPET and other substrates..  
Heat sealing threshold of PF-Polet381 D is lower than 105 °C.

Technical Data	Specification	Unit	Value	
	Thickness	µm	18	20
PF-Polet 381 D	Yield	m <sup>2</sup> / Kg	61.1	54.9
	Unit weight	g/m2	16.4	18.2

Logistic Data	MOQ (Minimum Order Quantity )
PF-Polet 381 D	40ft HC Container

## Benefits & Options

- \* Metalized
- \* Heat sealable (1 side)
- \* Treated (1 Side)
- \* Low SIT
- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (91/155EEC)
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)