


PF-Polet 381 D2

BOPP Film – Flexible Packaging



Application : High speed, heat sealable, white voided film for ice-cream packaging or wherever it is needed to have metallic surface on one side and white surface on the other side. Heat sealing threshold of PF-Polet381 D2 is lower than 95 °C.

Technical Data	Specification	Unit	Value		
	Thickness	µm	35	40	45
PF-Polet 381 D2	Yield	m ² / Kg	40.8	35.7	31.7
	Unit weight	g/m2	24.5	28	31.5

Logistic Data	MOQ (Minimum Order Quantity)
PF-Polet 381 D2	40ft HC Container

Benefits & Options

- * White voided metalized
- * Heat Sealable (1 side)
- * Treated (1 Side)
- * Ultra low SIT

- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)