


# PF-Polex 221 D

BOPP Film – Flexible Packaging



**Application :** General purpose packaging film for using on HFFS and VFFS machines. It can be used as single ply or as lamination substrate to itself and to other films. Heat sealing threshold of PF-Polex 221 D is lower than 105 °C.

Technical Data	Specification	Unit	Value				
	Thickness	µm	20	25	30	40	50
PF-Polex 221 D	Yield	m <sup>2</sup> / Kg	54.9	44.0	36.6	27.5	22
	Unit weight	g/m2	18.2	22.8	27.3	36.4	45.5

Logistic Data	MOQ (Minimum Order Quantity )
PF-Polex 221 D	40ft HC Container

## Benefits & Options

- \* Transparent
- \* Heat Sealable (2 side)
- \* Treated (1 Side)
- \* Low SIT

- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (91/155EEC)
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)