


PF-Polexmatt 251 S

BOPP Film – Flexible Packaging



Application : Suitable for lamination processes where matt effect is desired. Matt finish layer gives a non-reflective surface.

Technical Data	Specification	Unit	Value
	Thickness	μm	20
	Yield	m ² / Kg	58.1
	Unit weight	g/m2	17.2
PF-Polexmatt 251 S			

Logistic Data	MOQ (Minimum Order Quantity)
	40ft HC Container
PF-Polexmatt 251 S	

Benefits & Options

- * Matt
- * Heat sealable (2 side)
- * Treated (1 Side)
- * Conformity Declaration (FDA/ EU)
- * Material Safety Data Sheet (91/155EEC)
- * Food Grade Material / FDO Certified
- * Minimum order can include multiple types (negotiable for trials)