


# PF-Polexmatt 351 S

BOPP Film – Flexible Packaging



**Application :** Suitable for lamination processes where matt effect is desired. Matt finish layer gives a non-reflective surface. PF-Polexmatt351S can be used as printing substrate (for missing-dot-free printing) & lamination substrate to itself and to other films.

Technical Data	Specification	Unit	Value
	Thickness	µm	20
	Yield	m <sup>2</sup> / Kg	58.1
	Unit weight	g/m2	17.2
PF-Polexmatt 351 S			

Logistic Data	MOQ (Minimum Order Quantity )
PF-Polexmatt 351 S	40ft HC Container

## Benefits & Options

- \* Matt
- \* Heat sealable (1 side)
- \* Treated (1 Side)
- \* Conformity Declaration (FDA/ EU)
- \* Material Safety Data Sheet (91/155EEC)
- \* Food Grade Material / FDO Certified
- \* Minimum order can include multiple types (negotiable for trials)